

100W LED SHOEBOX LIGHT



Features


- · Lumileds LED, high luminous efficiency and long working life.
- High efficiency LED Driver, the wide range
- input voltage AC120-277V/AC200-480V. Die Cast aluminium cooling design, high quality
- ullet and better cooling for LED Tj < $85\,^{\circ}$ C. Excellent
- Optics design, greatly improve the light utilization and evenness.

Motion sensor Control Available (Option)



Product Applications

WISDOM LED SHOEBOX LIGHT series can be widely used in outdoor lighting(Wet location), Excellent for Museums, Art Galleries, Underground parking lot, Buildings, The lawn, Industrial areas, Residential areas, Sidewalks, Parking lot, Schools and etc, and many more applications.



















Shell materials: Aluminum & PC. Finish: Dark Bronze/White

Product Size:603mm*282mm*160mmCarton Size:570mm*350mm*150mm


• Net weight: 4.5Kg (9.9 lbs)


Structure Features



Specifications

Unit:inch(mm)







Technical Parameters

WSD-SB10W27-XXK-Z-TN-U-Y-#									
Power	100W	Lighting Angle	Type II, III, IV V						
Input Voltage	AC120-277V/AC200-480V	LED Brightness Decay	<5%/6000 hrs						
PF	>0.95	Working Life	>50000 hrs						
Driver Efficiency	>90%	Working Temperature	-30 - +45°C						
Luminous Flux	13000 Lm	Storage Temperature	-40 -+80°C						
Color Temperature	4000K/5000K	Protection Level	Wet Location/IP66						
CRI	Ra>70	Cable	3 core, 18AWG						
Optional dimming function	1-10Vdc	EPA	1.5FT ²						

Photometry





Example	: WSD-S	B10W27-X	(XK-Z[D,W,E	3,S]-TN[T2,	T3,T4,T5]-U[S,A,T]-Y[B	lank,P]-#	[Blank,M]
WSD	SB	10W	27	XXK	Z	TN	U	Υ	#
Conmpany	Product	Power	Voltage	Color Temp	Finish	Light Angle	Mounting Mean	Control	Control
	SB	10W(100W)	27	40K(4000K)	D(Dark Bronze)	T2(Type II)	S(slip fitter)	Р	M
WISDOM	SHOEBOX		AC120-277V	,	W(White)	T3(Type III)	A(Arm)	Photocell	Motion sensor
			48	±500K	B(Black)	T4(Type IV)	T(Trunnion)		
			AC200-480V		S(Silvery)	T5(Type V)			